

Peiltabelle Stahltank DIN 6608 und 6616

Nenninhalt: 10 000 Liter Tankdurchmesser: 2000 mm Gesamtlänge: 3780 mm

| cm | Liter | cm | Liter | cm | Liter | cm | Liter | cm | Liter |
|----|--------|----|--------|-----|--------|-----|--------|-----|---------|
| 1 | 6.0 | 41 | 1540.8 | 81 | 4077.7 | 121 | 6884.3 | 161 | 9377.4 |
| 2 | 16.9 | 42 | 1596.2 | 82 | 4146.9 | 122 | 6952.8 | 162 | 9430.5 |
| 3 | 31.1 | 43 | 1652.1 | 83 | 4216.2 | 123 | 7021.1 | 163 | 9482.8 |
| 4 | 47.8 | 44 | 1708.5 | 84 | 4285.7 | 124 | 7089.2 | 164 | 9534.6 |
| 5 | 66.8 | 45 | 1765.5 | 85 | 4355.3 | 125 | 7157.0 | 165 | 9585.7 |
| 6 | 87.8 | 46 | 1823.0 | 86 | 4425.0 | 126 | 7224.7 | 166 | 9636.1 |
| 7 | 110.6 | 47 | 1881.0 | 87 | 4494.8 | 127 | 7292.1 | 167 | 9685.8 |
| 8 | 135.1 | 48 | 1939.5 | 88 | 4564.8 | 128 | 7359.3 | 168 | 9734.9 |
| 9 | 161.2 | 49 | 1998.5 | 89 | 4634.8 | 129 | 7426.2 | 169 | 9783.2 |
| 10 | 188.7 | 50 | 2058.0 | 90 | 4705.0 | 130 | 7492.9 | 170 | 9830.8 |
| 11 | 217.7 | 51 | 2117.9 | 91 | 4775.2 | 131 | 7559.3 | 171 | 9877.6 |
| 12 | 248.0 | 52 | 2178.2 | 92 | 4845.5 | 132 | 7625.4 | 172 | 9923.7 |
| 13 | 279.5 | 53 | 2239.0 | 93 | 4915.8 | 133 | 7691.2 | 173 | 9968.9 |
| 14 | 312.3 | 54 | 2300.3 | 94 | 4986.3 | 134 | 7756.8 | 174 | 10013.4 |
| 15 | 346.2 | 55 | 2361.9 | 95 | 5056.7 | 135 | 7822.0 | 175 | 10057.0 |
| 16 | 381.3 | 56 | 2423.9 | 96 | 5127.2 | 136 | 7886.9 | 176 | 10099.8 |
| 17 | 417.4 | 57 | 2486.4 | 97 | 5197.8 | 137 | 7951.5 | 177 | 10141.7 |
| 18 | 454.6 | 58 | 2549.2 | 98 | 5268.3 | 138 | 8015.8 | 178 | 10182.7 |
| 19 | 492.8 | 59 | 2612.4 | 99 | 5338.9 | 139 | 8079.7 | 179 | 10222.7 |
| 20 | 532.0 | 60 | 2675.9 | 100 | 5416.5 | 140 | 8143.3 | 180 | 10261.8 |
| 21 | 572.2 | 61 | 2739.8 | 101 | 5487.1 | 141 | 8206.5 | 181 | 10299.9 |
| 22 | 613.2 | 62 | 2804.1 | 102 | 5557.7 | 142 | 8269.3 | 182 | 10337.0 |
| 23 | 655.2 | 63 | 2868.7 | 103 | 5628.2 | 143 | 8331.7 | 183 | 10373.0 |
| 24 | 698.0 | 64 | 2933.6 | 104 | 5698.7 | 144 | 8393.8 | 184 | 10408.0 |
| 25 | 741.7 | 65 | 2998.8 | 105 | 5769.2 | 145 | 8455.4 | 185 | 10441.8 |
| 26 | 786.2 | 66 | 3064.4 | 106 | 5839.6 | 146 | 8516.6 | 186 | 10474.4 |
| 27 | 831.6 | 67 | 3130.2 | 107 | 5909.9 | 147 | 8577.4 | 187 | 10505.8 |
| 28 | 877.7 | 68 | 3196.3 | 108 | 5980.2 | 148 | 8637.8 | 188 | 10535.9 |
| 29 | 924.5 | 69 | 3262.7 | 109 | 6050.5 | 149 | 8697.7 | 189 | 10564.7 |
| 30 | 972.2 | 70 | 3329.4 | 110 | 6120.6 | 150 | 8757.2 | 190 | 10592.0 |
| 31 | 1020.5 | 71 | 3396.3 | 111 | 6190.7 | 151 | 8816.1 | 191 | 10617.9 |
| 32 | 1069.6 | 72 | 3463.5 | 112 | 6260.6 | 152 | 8874.6 | 192 | 10642.1 |
| 33 | 1119.4 | 73 | 3530.9 | 113 | 6330.5 | 153 | 8932.6 | 193 | 10664.6 |
| 34 | 1169.8 | 74 | 3598.5 | 114 | 6400.2 | 154 | 8990.1 | 194 | 10685.3 |
| 35 | 1220.9 | 75 | 3666.4 | 115 | 6469.8 | 155 | 9047.1 | 195 | 10703.9 |
| 36 | 1272.7 | 76 | 3734.4 | 116 | 6539.3 | 156 | 9103.6 | 196 | 10720.3 |
| 37 | 1325.1 | 77 | 3802.7 | 117 | 6608.6 | 157 | 9159.5 | 197 | 10733.9 |
| 38 | 1378.1 | 78 | 3871.2 | 118 | 6677.8 | 158 | 9214.8 | 198 | 10744.1 |
| 39 | 1431.8 | 79 | 3939.9 | 119 | 6746.8 | 159 | 9269.6 | | |
| 40 | 1486.0 | 80 | 4008.7 | 120 | 6815.6 | 160 | 9323.8 | | |

Tabellenzahlen rechnerisch ermittelt, für amtliche Zwecke nicht geeignet. Aufgrund der üblichen Toleranzen und der unterschiedlichen Einbaubedingungen sind Abweichungen bis zu 6 % möglich.